



Double BALL BEARINGS CO, LTD

75 mm x 130 mm x 25 mm NTN 6215LLU deep groove ball bearings



Bearing No. 6215LLU

6215LLU Bearing 2D drawings and 3D CAD models

Size	75x130x25 mm
Bore Diameter	75 mm
Outer Diameter	130 mm
Width	25 mm
d	75 mm
D	130 mm
B	25 mm
C	25 mm
r min.	1,5 mm
da min.	83 mm
da max	90,5 mm
Da max.	122 mm
ra max.	1,5 mm
Weight	1,18 Kg
Basic dynamic load rating (C)	66 kN
Basic static load rating (C0)	49,5 kN
Reference speed	3 200 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359004991
Product Group	B00308
Enclosure	2 Seals



Double BALL BEARINGS CO, LTD

Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	75MM Bore; 130MM Outside Diameter; 25MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	2.6
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	5.118 Inch 130 Millimeter
Bore	2.953 Inch 75 Millimeter
Outer Race Width	0.984 Inch 25 Millimeter
bore diameter:	75 mm



Double BALL BEARINGS CO, LTD

precision rating:	ISO Class 0
outside diameter:	130 mm
finish/coating:	Uncoated
overall width:	25 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	25 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	25 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	3200 rpm
internal clearance:	CN
fillet radius:	1.5 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	5600 RPM
dynamic load capacity:	66000 N
series:	62
static load capacity:	49500 N
manufacturer product page:	Click here