



Double BALL BEARINGS CO, LTD

75 mm x 130 mm x 25 mm NTN 6215ZZ deep groove ball bearings



Bearing No. 6215ZZ

6215ZZ Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 75x130x25 mm |
| Bore Diameter | 75 mm |
| Outer Diameter | 130 mm |
| Width | 25 mm |
| d | 75 mm |
| D | 130 mm |
| B | 25 mm |
| C | 25 mm |
| rn | 0,5 mm |
| r min. | 1,5 mm |
| da min. | 83 mm |
| da max | 90,5 mm |
| Da max. | 122 mm |
| ra max. | 1,5 mm |
| Weight | 1,18 Kg |
| Basic dynamic load rating (C) | 66 kN |
| Basic static load rating (C0) | 49,5 kN |
| (Grease) Lubrication Speed | 4 800 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| EAN | 4547359005004 |
| Product Group | B00308 |



Double BALL BEARINGS CO, LTD

| | |
|---------------------------------|--|
| Enclosure | 2 Metal Shields |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 75MM Bore; 130MM Outside Diameter; 25MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste |
| Other Features | Deep Groove Shell Alvania Prelubricated |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.ntnamerica.com |
| Weight / LBS | 2.54 |
| Bore | 2.953 Inch 75 Millimeter |
| Outer Race Width | 0.984 Inch 25 Millimeter |
| Outside Diameter | 5.118 Inch 130 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| bore diameter: | 75 mm |
| precision rating: | ISO Class 0 |
| outside diameter: | 130 mm |



Double BALL BEARINGS CO, LTD

| | |
|------------------------------|----------------------------|
| finish/coating: | Uncoated |
| overall width: | 25 mm |
| bearing material: | High Carbon Chrome Steel |
| bore type: | Round |
| cage material: | Steel |
| closure type: | Double Shielded |
| inner ring width: | 25 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| outer ring width: | 25 mm |
| snap ring included: | Without Snap Ring |
| maximum rpm (grease): | 4800 rpm |
| internal clearance: | CN |
| fillet radius: | 1.5 mm |
| operating temperature range: | -40 to 120 ° C |
| maximum rpm: | 5600 RPM |
| dynamic load capacity: | 66000 N |
| series: | 62 |
| static load capacity: | 49500 N |
| manufacturer product page: | Click here |