



Double BALL BEARINGS CO, LTD



85 mm x 180 mm x 41 mm NACHI 6317 deep groove ball bearings

Bearing No. 6317

6317 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 85x180x41 mm |
| Bore Diameter | 85 mm |
| Outer Diameter | 180 mm |
| Width | 41 mm |
| d | 85 mm |
| D | 180 mm |
| B | 41 mm |
| C | 41 mm |
| r min. | 3 mm |
| da min. | 99 mm |
| Da max. | 166 mm |
| ra max. | 2.5 mm |
| Weight | 4.23 Kg |
| Basic dynamic load rating (C) | 133 kN |
| Basic static load rating (C0) | 96,5 kN |
| (Grease) Lubrication Speed | 3600 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling | No |



Double BALL BEARINGS CO, LTD

| | |
|---------------------------|--|
| Slot | |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 85MM Bore; 180MM Outside Diameter; 41MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage |
| Other Features | Deep Groove |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nachiamerica.com |
| Bore | 3.346 Inch 85 Millimeter |
| Outside Diameter | 7.087 Inch 180 Millimeter |
| Outer Race Width | 1.614 Inch 41 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 85 mm |
| Width | 41 mm |
| Fillet Radius/Chamfer | 3 mm |
| Dynamic Load Rating | 133,000 N |
| Static Load Rating | 96,500 N |



Double BALL BEARINGS CO, LTD

| | |
|-------------------------|-------------------|
| Limiting Speed - Grease | 3,800 rpm |
| Limiting Speed - Oil | 4,500 rpm |
| Factor f_0 | 13.3 |
| Radial Clearance | 0.012 to 0.036 mm |
| d_a (min) | 99 mm |
| D_a (max) | 166 mm |
| r_a (max) | 2.5 mm |